

Alpha-Pack-Bin APB 616-SN

equipped for roll-on roll-off vehicles, particularly suitable for different types of <u>bulky waste, mainly cardboard, paper or similar</u> <u>bulky and voluminous waste or secondary raw materials</u>.

## Technical Details:

Integrated one-level hydraulic aggregate, compaction system: horizontal packer blade, container walls are reinforced by welded steel profiles with a distance of 600mm, side hinged discharge door with robust, secure triple locking device, packer blade control gives 100% compaction force over the complete cycle of 1.500mm.

## standard equipment of machine:

\* hook points on both sides, hook height can be adjusted to 1.450 mm or

- 1.570 mm (fold down front hook, fixed hook on discharge door)
- \* plastic roller in front and at rear


\* side hinged discharge, secure triple locking device

\* pendulum roof for easy emptying

\* single pump

\* oil deficiency switch

- \* oil drip tray and central rainwater drain close to the tank room
- \* 2-component coating (80 µm) in RAL colour as requested



		Stand: 01.02.2021	Index:	005	All indicated dimensions are approximate dimensions! Subject to technical modification							
power:	5,5 kW		capacity	maximum operating	Theoretical cylinder	Theoretical blade face	net weight	" A "	"в"	" C "	"D"	
fuse protection:	C 25A	Туре	[ m <sup>3</sup> ]	pressure [ bar ]	thrust [ kN ]	pressure [ N / cm <sup>2</sup> ]	[ kg ]	[mm]	[ mm ]	[mm]	[mm]	
electrical connection:	400 V, 50 Hz, clockwise											
forward/return cycle speed:	35 sec. / 36 sec.	APB 616 - SN / 15	15	200	314	23,3	5.070	6.230	6.050	5.830	3.100	
		APB 616 - SN / 18	18	220	346	25,6	5.220	6.830	6.650	6.430	3.700	
displaced volume:	1,95 m³	APB 616 - SN / 20	20	220	346	25,6	5.450	7.430	7.250	7.030	4.300	
capacity charge box:	3,60 m³	APB 616 - SN / 23	23	220	346	25,6	5.710	8.030	7.850	7.630	4.900	